

CLEANING SEALING & AFTERCARE

POWERSTRIPPER TECHNICAL DATA SHEET

REF: 16/5/1 MARCH 2017



LTP POWERSTRIPPER

High Performance Intensive cleaner

For interior & exterior use

Suitable for travertine, stone, sandstone, slate, marble, porcelain, granite, terracotta, quarry, brick, concrete and external paving.

For stripping and cleaning of vitrified glazed ceramics, travertine, natural stone, sandstone, slate, marble, granite, terracotta, quarry, brick, concrete, external paving, terrazzo and other mineral floors & walls. Helps remove old layers of sealer, oxidised linseed oil and other mineral oils.

Directions for use

For application and cleaning tools see LTP website.

To establish whether the tiles are colour fast and to determine optimal dilution for LTP Power Stripper, always test on an inconspicuous area prior to general application.

Surface cleaning: 1:12 in warm water

Deep stripping: 1:6 in warm water

In extreme cases: 1:4 in warm water (e.g. Removal of linseed oil)

Sweep or dry mop floor to remove grit and surface dirt. Mix solution according to required dilution. Working in manageable sized areas, mop on solution to thoroughly wet floor. Leave for 5 - 10 minutes, keeping floor damp with further solution should it begin to be absorbed. Agitate surface using a mildly abrasive pad. If the floor will stand up to it, machine scrub with a stripping pad. Remove resulting dirty residue using clean warm water and absorbent cloths. If treating a large area a wet vacuum will prove helpful. Rinse thoroughly and allow to dry completely before applying further treatments. You may need to repeat washing process a couple of times on severely contaminated surfaces.

Coverage

Surface cleaning:	60sqm per litre
Deep stripping:	30sqm per litre
In extreme cases:	15sqm per litre

Notes

Important: Protect plastics, lino, painted and other sensitive surfaces against splashes. This product should not be used for every day cleaning of floors that are sealed.

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 5 years

Health, Safety & Environmental

Causes serious eye damage.

Keep out of reach of children. Wear protective gloves/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. Dispose of contents/container to a waste collection point in accordance with local authority requirements.

DANGER



Contains less than 5% anionic surfactants.

Ingredients: www.ltp-online.co.uk/dr

Contains: REACTION PRODUCT OF BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. AND BENZENESULFONIC ACID, 4-METHYL- AND SODIUM HYDROXIDE; 2- BUTOXYETHANOL; 2,2'-IMINODIETHANOL



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+44 (0) 1823 666213 | www.ltp-online.co.uk | info@ltp-online.co.uk
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK

