

CLEANING SEALING & AFTERCARE

GROUT STAIN REMOVER TECHNICAL DATA SHEET

REF: 8/5/1 MARCH 2017



LTP GROUT STAIN REMOVER

Cement, Limescale & Grout Residue Remover

A rapid action cleaning agent for removing cement residues, grout stain, efflorescence and other similar deposits. May be used in dilute or concentrated form.

Interior & Exterior use

For glazed and un-glazed ceramics, slate, quarry tiles, brick, terracotta & acid resistant natural stones.

Directions for use

For application and cleaning tools see LTP website.

In mild cases and on absorbent tiles:

Dilute 1 part Grout Stain Remover in 4 parts water. Apply with a cloth or sponge wrung out in the solution. Wipe off thoroughly with a clean damp cloth.

In more severe cases:

Dilute 1 part Grout Stain Remover in 1 part water. Apply liberally and spread over surface of tiles. If necessary, agitate with a scrubbing brush and leave to react for 5-10 minutes, keeping wet with additional Grout Stain Remover solution. Mop up and rinse thoroughly with clean water.

In extremely severe cases:

Use undiluted and agitate with scrubbing brush or mechanical scrubber if necessary. Neutralise treated surface with clean water after use.

N.B. Always rinse surfaces thoroughly with clean water.

Coverage

Approximately 5-25m² per litre.

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 5 years

Notes

Not suitable for use on surfaces that are calcareous, sensitive to acids (e.g. stainless steel, chrome, enamel etc), or contain lime (i.e. marble, travertine, limestone, engineered stone & sandstone containing iron). In conditions of extreme humidity LTP Grout Stain Remover vapour may react with acid sensitive surfaces. Any contaminated surface should be rinsed off immediately with plenty of **clean water**. Do not use when under floor heating systems are in operation.

Important: – Always test the solution on a small inconspicuous area prior to general application. Work in manageable sized areas. Prolonged contact with grout joints should be avoided.

Health, Safety & Environmental

Contains Hydrochloric Acid <10%.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Avoid breathing spray.

Keep away from food, drink and animal feeding stuffs.

Dispose of contents/container to hazardous waste collection point.

Label in Accordance With (EC) No 1272/2008



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+44 (0) 1823 666213 | www.ltp-online.co.uk | info@ltp-online.co.uk
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK



Federation
Stone
Great Britain

