



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

CRACKLE GLAZE PROTECTOR TECHNICAL DATA SHEET REF: 29/5

LTP CRACKLE GLAZE PROTECTOR

Impregnating Sealer

For Interior use only

Suitable for ceramic tiles that have a porous crackle glaze.

Forms a clear colourless barrier. Helps protect porous tiles from penetration by water, dirt, oil, grease, limescale and other commonly found household contaminants. For use on crackle glaze tiles and grout joints.

Directions for use

Ensure that the tile surface is clean and dry. Any tiles that are to be wet cut should be protected with at least one coat of sealer. Once the tiles have been fixed and before grouting apply one coat of sealer to the surface with a sponge or soft cloth and then buff immediately into the surface with a separate soft cloth. This should be done until all excess is removed. Leave for a minimum of two hours before grouting with normal grouts.

If coloured or pigmented grouts are used: Apply two coats and do not buff off excess. Leave for a minimum of 24 hours. Sponging off residual grout will remove excess sealer.

Once the grouting is dry (min 24hrs) apply a second coat of sealer to the surface also covering the joints. After 48 hours the surface can be cleaned as normal. Use a dry cloth to remove any excess from non-absorbent surfaces. Use only in well ventilated areas.

Drying Time: Approximately 30 – 40 minutes. Becomes fully effective after approximately 48 hours.

Use only in well ventilated areas. Do not breathe vapours.

Coverage

Approximately 5 sq.m per 500ml (2 coats)

Maintenance

Wash tiles with a mild, non acidic detergent.
LTP Stonewash Spray

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 4 years for un-opened containers.

Health & Safety

Contains: White Spirit: naptha (petroleum) hydrodesulphurised heavy (<0.1% benzene). Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Store locked up. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Wear protective gloves. If ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention. Dispose of contents/container to hazardous waste collection point.

Important

Protect sensitive surfaces against splashes. Always test the product in an inconspicuous area prior to general application. Do not use in direct sunlight. All spillages should be wiped up immediately. LTP Crackle Glaze Protector is not suitable for use on tiles that have been grouted with an epoxy grout.

DANGER



VOC STATEMENT

EU Limit value for this product (Cat A/h) 750g/L (2010)
This product contains max 710g/L VOC

UN 1300

EC Label EC No 1272/2008



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

January 2013

