



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

STONE OIL ANTIQUE TECHNICAL DATA SHEET REF: 27/5/1

LTP STONE OIL ANTIQUE

Pre- Polish Ageing Oil

Suitable for natural stone and terracotta.

For Interior & Exterior use

A unique pre-polish oil for making new stone and terracotta look instantly "aged"

Directions for use

Ensure surface to be treated is completely dry and free from contaminants which may prevent LTP Stone Oil Antique from properly curing. Apply by brush or soft cloth and allow to cure thoroughly (minimum 12 hours) before polishing with LTP Antique Wax. The action of applying the wax removes some of the LTP Stone Oil Antique and it is the remaining LTP Stone Oil Antique beneath the polish which provides the "aged" appearance. The longer the oil is allowed to cure, the more difficult it is to remove and the darker the finish will be. For an even darker finish a second coat may be applied and allowed to cure thoroughly. This should be done before use of the wax.

Use only in well ventilated areas. Do not breathe vapours.

Coverage

Approximately 10 sq m per litre (one coat)

Maintenance

Avoid using strong detergents and kitchen cleaners to wash surfaces finished with LTP Antique Wax. Use LTP Waxwash to wash the floor and buff when dry. Re-polish any dull areas with LTP Antique Wax.

Notes

IMPORTANT: If using this product outside finish with a coat of LTP Mattstone to offer extra protection. Experiment before general application, so that methods of use are fully understood. On more absorbent stone or terracotta it may be necessary to use a suitable impregnating sealer before application of LTP Stone Oil Antique, e.g LTP Boiled Linseed Oil or LTP Mattstone. Shake bottle before use. Used cloths should be burnt after use as they may spontaneously combust. Allow good ventilation during application. LTP Stone Oil Antique may cure more rapidly in dry or higher temperature conditions. Avoid working in direct sunlight; rapid oxidation may inhibit effectiveness of the product. Not suitable for older floors that have no damp proof course.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

January 2015

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 4 years for un-opened containers.

Health & Safety

Contains: White Spirit (naphtha (petroleum), hydrodesulphurised heavy (<0.1% benzene)). Toxic to aquatic life with long lasting effects. May be fatal if swallowed and enters airways.

Keep out of the reach of children. Store locked up. IF SWALLOWED: Immediately call a doctor, Do NOT induce vomiting. Avoid release to the environment. Collect spillage. Store in a closed container. Dispose of contents/container to hazardous waste collection point.



Danger

VOC STATEMENT

EU Limit value for this product

(Cat A/h) 750g/L (2010)

This product contains max 597g/L VOC

UN 1263

EC Label EC No 1272/2008

