

SRA800/ SRA950F



The SRA800 and SRA950F are ride-on brush cutters capable of cutting grass and thick vegetation right up to saplings. Their low height aids stability when used on slopes.

Both machines are powered by Kawasaki electric start petrol engines - 16hp and 24hp respectively and have hydrostatic drive, with 4WD for the SRA950F. Cutting widths are 80 or 95cm.



KEY FEATURES

Power: 16ps or 24ps

Drive System: V-Belt

Special Features: Low centre of gravity, capable of cutting fine grass up to saplings, compact and maneuverable

		SRA950F	SRA800
Power	Engine	Kawasaki FS691V 24ps	Kawasaki FS481V 16ps
	Fuel capacity	14ltr	14ltr
Transmission	Type	HST (Hydrostatic transmission) 13cc	HST (Hydrostatic transmission) 10cc
	Slope Capability	25 degrees	15 degrees
	Driving System	On Demand 4WD	2WD
Brakes	Type	Internally expanding	Internally expanding
	Diff Lock	Standard	Standard
	Minimum Turning radius	2100mm	1750mm
Tyres	Front	4.00- 7	3.5-7
	Rear	17 x 8.00- 8	16 x 7.00- 8
Speed	Forward	10kmph	Low 5.8kmph - High 10kmph
	Reverse	8.5kmph	Low 3.5kmph - 6kmph
Dimensions	Length	1965mm	1840mm
	Width	1090mm	920mm
	Overall height	955mm	905mm
	Ground Clearance	125mm	105mm
	Weight	330kg	250kg
Mower Deck	Blades	Single blade with two swing tips (reversible)	Single blade with two swing tips (reversible)
	Rear discharge rotary		
	Cutting width	950mm	800mm
	Cutting height	35mm- 125mm	20mm- 90mm
	Adjustments	Stepless dial	Stepless dial

