

TG6675 PS



The TG6675 PS compact tractor is available with a ROPS or a factory fitted, fully air-conditioned category 2 cabin. It features a 65hp four cylinder, Stage IIIB diesel engine, with a F12/R12 power-shuttle transmission. The rear, category 1 & 2, 3-point linkage has a capacity of 1,600kg at ball end and 1,500kg at 24 inches.

Draft control, two auxiliary valves and a front loader joystick are all as standard. The rear PTO is 2-speed with a mid PTO also included with the cabin model. An optional front loader is available. It is supplied with either Turf or Ag tyres.

With excellent visibility and manoeuvrability, the ISEKI TG6675 is perfect for all of your golf and sports turf tasks.



KEY FEATURES

Power: 48.5kW (65hp)

Lift capacity: 1,600kg at ball end or 1,500kg 24" behind

Special features: Light footprint, compact, class leading lift capacity, electronic shuttle with fingertip control and mechanical gearbox

Power	Engine: Type	N4LDI-TA4503
	Displacement (L)	2216
	No of cylinders	4
	Power	48.5kW (65hp) at 2600rpm
	Fuel capacity	53ltr
	Rated engine speed	2600rpm
Transmission	Main Clutch	Multi Wet
	Gear forward/reverse	F12/R12
	Differential Lock	Standard
	Front Axle Type	4WD/2WD
	Steering	Power Steering
	Tilt steering	Standard
Brakes	Type	Wet discs
Tyres	Type	Turf or Ag
	Front	9.5-16
	Rear	13.6-28
PTO	Clutch	Independent (2 modes)
	Rear PTO Speed	540/ 750
	Mid PTO at engine rpm	2000 (35mm diameter of shaft)
Hydraulics	3-point lift capacity	1600kg at ball end or 1500kg 24" behind
	Pump capacity	74.6L/min
	Position control	Standard
	Draft control	Standard
	Auxiliary valve	2 banks
	Joystick valve	Standard
3P Linkage	Category	1
	Lift Rod and check chain	Turn buckle
	Lower link end	Hook end Cat 2
	Rear hitch	Clevis Drawbar
Electric	Combination Switch	Column type
	Digital Panel	Standard
ROPS	Type	Rear foldable
Cabin	Air conditioned/heater	Optional
Dimensions	Length	3.57m
	Width	1.48m
	Height	2.64m with ROPS or 2.34m with cabin
	Weight	1930kg with ROPS or 2090kg with cabin
	Wheelbase	2.04m