



TH4295/ TH4335/ TH4365



To get the most from your investment you need to be able to use your tractor for a multitude of jobs. The TH range from ISEKI fits the bill perfectly - designed for versatility, maximum comfort and ease of use.

Excellent performance and high efficiency comes standard with the TH range, making short work of the most demanding operations. The TH4435 mechanical which includes a crawler is also available with a 12 speed mechanical transmission.



KEY FEATURES

Power: 28hp, 32.5hp or 35.7hp

Lift capacity: 1,110kg at ball end

Special features: Soft-start PTO, advanced hydrostatic transmission and comfort with the option of a cab, ISO mounted operators platform

 @iseki_uk

www.iseki.co.uk



		TH4295	TH4335 (TH4335 mech)	TH4365
Power	Engine: Type	Diesel E3CD InDirect Injection OHV	Diesel E3CD InDirect Injection OHV	Diesel E3CG InDirect Inj OHV
	Aspiration	Natural	Natural	Natural
	No of cylinders	3	3	3
	Power	20.9kW (28hp)	24.2kW (32.5hp)	26.6kW (35.7hp)
	Fuel capacity	35ltr	35tr	35ltr
	Rated engine speed	2600rpm	2600rpm	2600rpm
Transmission	3 Range	3 range HST	3 speed sliding mesh (F3-R1 sliding m) 3 speed sliding mesh	
			Or F12/R12 Mechanical with creep	
	Gear speeds	3 gears forward, 3 reverse	3 gears forward, 3 reverse (9 fwd,3 rv)3 gears forward, 3 reverse	
	Clutch	None	None (single stage 240mm disc) None	
	Speed		
	Steering	Power Steering	Power Steering	Power Steering
Brakes	Type	Wet discs	Wet discs	Wet discs
Tyres	Type	Turf or Ag	Turf or Ag	Turf or Ag
	Front	24 x 8.5-12- PR (turf) 6-14-4PR (ag)		
	Rear	315/80D-16-6PR (turf) 12.4-16-4PR (Ag)		
PTO	Type	Independent, engine driven		
	Clutch	Hydraulically engaged, multi-plate wet disc		Hydraulically engaged, multi-plate wet disc
	Rear PTO Shaft	540 PTO min-1@ 2,484 min-1 engine speed		540 PTO min-1@ 2,484 min-1 engine speed
		1000 PTO min-1@ 2,291 min-1 engine speed		1000 PTO min-1@ 2,291 min-1 engine speed
	Mid PTO Speed	2000rpm @ 2500rpm		2080rpm@ 2600rpm
		Speed @ ers: 1,507 @ 2,600 min-1		Speed @ ers: 1,595 @ 2,600 min-1
		Speed @ ers: 1,921 @ 2,600 min-1		Speed @ ers: 2,004 @ 2,600 min-1
Hydraulics	Hydraulic output	Total: 45.6L/min, Main system: 32L/min		
	Rear linkage type	3-point hitch	3-point hitch	3-point hitch
	Rear linkage size	Category 1	Category 1	Category 1
	Lift capacity	1,100kg at ball end, 730kg 24" behind		
Charging	ROPS Type	40 amp alternator with internal regulator/rectifier		
Dimensions	Length	3.12m	3.12m	3.12m
	Width	1.28m (Turf) 1.43m (Ag)		
	Height over ROPS	2.41m on Turf tyres or 2.45m on Ag tyres		
	Weight with ROPS	1155kg onTurf tyres or 1170kg on Ag tyres		
	Wheelbase	1.69m	1.69m	1.69m