

Contour power module

Contour has a modern, curved appearance displaying many design features like our new lateral fuse carrier, internal segregation between power and data and comes complete with plastic clips on the covers so there are no visible fixing screws and fully compliant to current safety regulations.

Available
now with
international
sockets

Flame retardant ABS
plastic body with a
choice of fascia colours

Lateral fuses with a choice
of 3.15A or 5A to comply
with BS 6396:2008

Choose from power,
data, audio, USB, and
international sockets

- Power & data cables all exit from the back of the unit unless on a slatwall/tool rail where cables exit from the bottom of the unit
- Unit complies with BS 5733
- All standard options are supplied with a 1m mains lead to 3 pole connector and 3m data lead where relevant
- Requires a separate mains lead if connected directly to a socket
- Will accept Category 6 data sockets if specified
- Fixing via Contour 'C' Clamp or adhesive fixing kit



Manage your energy

Configure Contour to allow energy to be monitored and controlled with Footprint. See page 89 for more details.

*Please note that 6 tiles is the maximum number of power and/or data sockets, and maximum length is 362.5mm.

power module *Contour*



Black



Grey



All White



All Black

Code	Colour	Description
94PS04	Black	2 x Power Sockets
94PS01	Grey	3.15A individually fused, supplied with 1m mains lead to male 3 Pole Connector plug.
94PS07	All White	
94PS10	All Black	
94PS06	Black	4 x Power Sockets
94PS03	Grey	3.15A individually fused, supplied with 1m mains lead to male 3 Pole Connector plug.
94PS09	All White	
94PS11	All Black	
94US03	Black	2 x Power Sockets, 2 x RJ45 Cat5e Data Sockets
94US01	Grey	3.15A individually fused, supplied with 1m mains lead to male 3 Pole Connector plug and 3m data leads.
94US05	All White	
94US07	All Black	
94US04	Black	4 x Power Sockets, 2 x RJ45 Cat5e Data Sockets
94US02	Grey	3.15A individually fused, supplied with 1m mains lead to male 3 Pole Connector plug and 3m data leads.
94US06	All White	
94US08	All Black	

Note: Fuses only accessible after removal of equipment plug. Lead lengths shown will be the conductor length and not the distance from the end of the module to the plug. For example, a 3m prewired power lead will be approximately 2.875m as 125mm will be internal for the termination, this is also applicable for data leads.

Cables: White cables are supplied with White & Grey modules and Black cables with Black modules.



Build it your way

UK Sockets:

UK NS/ Ang Fused & Unfused
Round Earth NS / Ang Fused & Unfused
T' Earth NS Fused & Unfused

International Sockets:

American Australian
French/Belgium German
Indian Italine
Swiss IEC C13
IEC C19

In-Feeds

Hard Wired Mains Cable 1.5mm
Hard Wired SY Cable 1.5mm
3 Pole Connector Tail 1.5mm

Data, Telecommunications, AV:

3.5mm Audio Phono
9 Pin D Data RJ11 Tel Shuttered
BT Tel Shuttered RJ45 Cat5e
Co Axial RJ45 Cat6
Data Spool USB
Ethernet BNC S Video
HDMI SVGA
USB-HUB

Circuit Protection, Switching, Indication:

Ammeter Neon Indicator
Filter RCD
MCB RCBO
Varistor
Switch - Double Pole (16A Max Supply)
Switch - Single Pole (16A Max Supply)


Accessories for Contour

Adhesive Fixing Kit

Adhesive Kit, 1 Kit required per module

Code

440006




'C' Clamp - Contour

We recommend using 2 x 'C' Clamps for any module with more than 2 sockets. Fits desk thickness between 20mm-32mm

Code

440371



On Desk

In Desk

Under Desk

Accessories