

YewdaleDefiant® dart fabric


shading efficiency

Transmittance is the amount of light and heat transmitted beyond the fabric. The lower the amount, the greater the efficiency.

Block/reflect is the amount of heat and light that is blocked or reflected. The higher the amount, the greater the efficiency.

Absorption is the amount of heat and light bsorbed in the fabric. The higher the amount, the lower the efficiency.

Ultraviolet protection illustrates how protective the fabric is against ultraviolet rays. The higher the amount, the greater the effectiveness.





this fabric is GREENGUARD certified as a low emissions product suitable for indoor use.

	3000 mm	2500 mm	1830 mm	127mm / 89	Heat Transmittano	Light Transmittano	Shading Co-efficiency	Light Reflection %	Sun Block & L Protection %	Absorption %	Heat Reflecti
White					0	0	0.33	83	100	27	73
Vanilla					0	0	0.33	83	100	30	69
Beige					0	0	0.38	71	100	37	63
Magnolia					0	0	0.32	83	100	35	65
Grey					0	0	0.45	57	100	49	51
Iron					0	0	0.59	30	100	71	29
Black					0	0	0.71	5	100	95	5
Burgundy					0	0	0.42	7	100	83	17
Bottle Green					0	0	0.55	14	100	92	8
Navy					0	0	0.39	8	100	91	9
Pink					0	0	0.41	62	100	34	66
Mint Green					0	0	0.41	60	100	34	66
Sky Blue					0	0	0.41	62	100	36	64
Black / White					0	0	0.33	83	100	27	73

Please enquire about other fabrics that we have available...



















harrier

thames

dart

YewdaleDefiant® dart fabric

The YewdaleDefiant® Dart fabric is designed for areas where a high level of light exclusion is required along with exceptional performance characteristics. The flame retardant fibreglass composition with a PVC coating for easy cleaning, ensures this fabric is suitable for almost all applications. With 14 colours and the most advanced range of fabric widths available, fabric joins are kept to a minimum to assist in wastage, design and speed of fabrication. This fabric comes with a full Biosafe® accreditation due to the antimicrobial properties of the fabric which inhibit the spread of bacteria, which has been tested under stringent conditions.

Fabric Composition: 4-ply; 75% PVC, 25%

Fibreglass

14 Fabric Range:

Louvre Widths: 127mm (5") 89mm (3.5") 100m

Vertical Roll Length: Roller Fabric Width:

1830mm (72") 2500mm (98.4") 3000mm (118.11")

Roller Fabric Length: 30m Fabric Thickness:

0.25mm - 0.33mm 407 g/m² - 12oz/syd Fabric Weight: Fire Retardancy:

Conforms to BS5867, Part 2: Type B 2008

IMO Certified: IMO 2010 FTP CODE ANNEX1PART7

Shading: Blackout. Suitable

for computer environments

Moisture Resistance: Suitable for moist conditions

Anti Bacterial: Biosafe® Accreditation Care Instructions: Wipe clean with a

mild 5% detergent

solution

this fabric range comes with a full **LIFETIME** Warranty as standard.

this fabric range comes with a full **BIOSAFE**® Accreditation as standard.



White



Black White











